

SAFETY DATA SHEET

ProCare Air Freshener

UNICARE (CHEMICALS) LTD

1 Identification

Product Identifier:

Procure Air Freshener

Other means of identification:

Not applicable.

Recommended use of the chemical and restriction on use:

Space fragrance

Supplier's details:

Unicare (Chemicals) Ltd,
Aradhippou Industrial Area 7101,
Larnaca, Cyprus, P.O Box 54088
Tel.: +357 24531766, +357 24533765
Fax: +357 24532111
Email: team@unicaregroup.com

Emergency phone number

1401

2 Hazard(s) identification

Classification of the substance or mixture

According to regulation (EC) No 1272/2008 [CLP]

Serious Eye Damage / eye irritation: Hazard Category 1

Flammable liquid: Hazard Category 2

Skin corrosion / Irritation: Hazard Category 2

Specific target organ toxicity—single exposure: Hazard Category 3

GHS Label Element



Signal Word:

Danger

Hazard Statements:

Causes serious eye damage.
Highly flammable liquid and vapour.
Causes skin irritation.
May cause drowsiness or dizziness.

Precautionary Statement

Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash your hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.
Take off contaminated clothing and wash before reuse.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Take any precaution to avoid mixing with combustibles materials.
In case of fire: Use Pulverized water, foam, dry chemical & carbon dioxide for extinction.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

Immediately call a POISON CENTER or doctor/physician.

Store locked up.

Dispose of contents/container to waste according to national / local regulations.

Other hazards which do not result in classification

Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

Mixture

Description	- CAS Number - EINECS Number - Reach registration number	Concentration (% w/w)	Note / Classification
Isopropyl alcohol	- 67-63-0 - 200-661-7 - N/A	40 - 45	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336
Alcohol ethoxylated	- 66455-14-9 - 500-165-3 - N/A	5 - 6	Aquatic Acute 1, H400; Aquatic Chronic 3, H412; Eye Dam. 1, H318; Skin Irrit. 2, H315; Acute Tox. 4 (oral), H302
Quaternary Ammonium Compounds	- 63449-41-2 - 264-151-6 - N/A	0.25 – 0.35	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1B, H314; Aquatic Acute 1, H400

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

4 First-aid measures

Description of first aid measures

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, and consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms/effects, acute and delayed

Most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further important symptoms and effects are so far not known.

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5 Fire-fighting measures

Extinguishing media

Flash Point & Method

None

Suitable Extinguishing Media

Pulverized water, foam, dry chemical & carbon dioxide

FIRE HAZARD. Flammable. INDIRECT FIRE HAZARD. May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard.

Specific hazards arising from the chemical

Carbon monoxide, carbon dioxide, formaldehyde as well as other toxic vapours and gases which are common to thermal degradation (in case of fire) of organic compounds.

Special protective actions for fire-fighters

Wear self-contained breathing apparatus and full protective gear.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures see, Section 8.

Environmental precautions

No special precautions required.

Methods and materials for containment and cleaning up

For containment:

Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapour with water curtain. Provide equipment/receptacles with earthling. Do not use compressed air for pumping over spills.

Methods for cleaning up: Take up liquid spill into absorbent material, e.g.: dry sand/earth/vermiculite or powdered limestone.

Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Carefully collect the spill/leftovers.

Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

7 Handling and storage

Precautions for safe handling

Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Use spark-/explosion proof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe normal hygiene standards. Keep container tightly closed.

Protection against fire and explosion

Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosion-proof appliances and lighting equipment. Keep containers closed.

Conditions for safe storage, including any incompatibilities

Incompatible products: Strong oxidizers.

Incompatible materials: Direct sunlight. Heat sources. Sources of ignition.

Heat-ignition: KEEP SUBSTANCE AWAY FROM: heat sources. Ignition sources.

Storage stability:

Store in a cool area. Store in a dry area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing.

Packing material:

SUITABLE MATERIAL: Teflon, polyethylene, polypropylene, zinc

Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

8 Exposure controls/personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:

Isopropanol (CAS:67-63-0)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	200 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TWA: Time-Weighted Average concentration

STEL: Short Term Exposure Limit

PEL: Permissible Exposure Limit

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protective equipment

Respiratory protection:

Respiratory protection in case of vapour/aerosol release. (Particle filter EN 143 P2 or FFP2)

Hand protection:

Chemical resistant protective gloves. (EN 374)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374):

e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (cage goggles) (e.g. EN 166) and face shield.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work.

Handle in accordance with good industrial hygiene and safety practice.

9 Physical and chemical properties

Physical and chemical properties

General Information

- **Appearance:**

Form: Liquid

Colour: Clear

- **Odour:** Characteristic

- **Odour threshold:** Not determined

- **pH-value:** 7.0 – 7.5

- **Specific gravity:** 0.97 – 0.99

- **Change in condition**

Melting point/Melting range: Not determined

Boiling point/Boiling range: Not determined

- **Flash point:** Not determined

- **Flammability (solid, gaseous):** Not applicable

- **Ignition temperature:** Not applicable

- **Decomposition temperature:** Not determined

- **Self-igniting:** Product is not self-igniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapour pressure at 20 °C:** Not determined

- **Density at 20 °C:** Not determined

- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined

- **Viscosity:**

Dynamic: Not determined
Kinematic: Not determined

10 Stability and reactivity

Reactivity

May react violently with oxidants.
Prolonged storage/in large quantities: may form peroxides.

Chemical stability

No specific test data related to reactivity available for this product or its ingredients.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

Conditions to avoid

See SDS Section 7 - Handling and storage.

Incompatible materials

Substances to avoid:
Avoid contact with oxidising agents (e.g. nitric acid, peroxides and chromates).
Strong acids

Hazardous decomposition products

In case of fire: carbon dioxide, carbon monoxide

11 Toxicological information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Toxicological (health) effects

Acute toxicity: Assessment: Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Assessment: Irritant to skin.

Serious eye damage/irritation: Assessment: Cause serious eye damage.

Respiratory or skin sensitisation: Assessment: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Assessment: Based on available data, the classification criteria are not met.

Carcinogenicity: Assessment: Based on available data, the classification criteria are not met.

Reproductive toxicity: Assessment: Based on available data, the classification criteria are not met.

STOT-single exposure: Assessment: Hazard Category 3; May cause drowsiness or dizziness.

STOT-repeated exposure: Assessment: Based on available data, the classification criteria are not met.

Aspiration hazard: Assessment: No aspiration hazard expected.

Symptoms related to the physical, chemical and toxicological characteristics: Not available data.

Numerical measures of toxicity (such as acute toxicity estimates): Not available data.

Toxicological Data: Isopropyl Alcohol (2-Propanol) (CAS: 67-63-0)

LD₅₀ oral rat:

5045 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 5840 mg/kg body weight; Rat)

LD₅₀ dermal rabbit:

12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)

LC₅₀ inhalation rat (mg/l):

73 mg/l/4h (Rat)

ATE US (oral):

5045.000 mg/kg body weight

ATE US (dermal):

12870.000 mg/kg body weight

ATE US (vapours):

73.000 mg/l/4h

ATE US (dust, mist):

73.000 mg/l/4h

Toxicological Data: Alcohol Ethoxylate (CAS: 66455-14-9)

The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

Acute toxicity:

Assessment of acute toxicity: Of moderate toxicity after single ingestion.

Experimental/calculated data: LD50 rat (oral): 500 - 2,000 mg/kg

Irritation:

Experimental/calculated data:

Skin corrosion/irritation: non-irritant

Serious eye damage/irritation rabbit: irreversible damage (Draize test)

13 Ecological information

Toxicity:

Eco toxicity

No relevant information available.

Persistence and Degradability

No relevant information available.

Bioaccumulation

No relevant information available.

Mobility in soil

No relevant information available.

Other Adverse Effects

No relevant information available.

Ecological Data: Isopropyl Alcohol (2-Propanol) (CAS: 67-63-0)

LC50 fish 1:

4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)

EC50 Daphnia 1:

> 10000 mg/l (48 h; Daphnia magna)

LC50 fish 2:

9640 mg/l (96 h; Pimephales promelas; Lethal)

EC50 Daphnia 2:

13299 mg/l (48 h; Daphnia magna)

Threshold limit algae1:

> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)

Threshold limit algae 2:

1800 mg/l (72 h; Algae; Cell numbers)

Ecological Data: Alcohol Ethoxylate (CAS:66455-14-9)

Toxicity to fish:

LC50: (96 h) 1 - 10 mg/l, Brachydanio rerio

Aquatic invertebrates:

EC50 (48 h): 1 - 10 mg/l, Daphnia magna. Literature data.

Aquatic plants:

EC50: (72 h) 1 - 10 mg/l, Scenedesmus subspicatus. Literature data.

Microorganisms/Effect on activated sludge:

EC10: > 1,000 mg/l, activated sludge (DEV-L2)

Chronic toxicity to aquatic invertebrates:

No observed effect concentration: 0.1 - 1 mg/l. Literature data.

13 Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

14 Transport information

UN Number: ADR/RID, IMDG, IATA: UN1993

UN Proper Shipping Name: ADR/RID, IMDG, IATA: Flammable liquid, N.O.S. (isopropanol (isopropyl alcohol)).

Transport hazard class(es): 3

Packing group, if applicable: II

Environmental hazards: Not applicable.

Special precaution for user: Danger: Flammable Liquid (see section 7)

Transport in bulk according to Annex II of Marpol 73/78 and the IBCcode: Not applicable.

15 Regulatory information

Safety, health and environmental regulations specific for the product in question

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I:** None of the ingredients is listed.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Abbreviations and acronyms:**

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PEL: Permissible Exposure Limit

PNEC: Predicted No-Effect Concentration

STEL: Short Term Exposure Limit

TWA: Time-Weighted Average concentration

VOC: Volatile Organic Compounds, USA, EU

vPvB: very Persistent and very Bioaccumulative

H225: Highly flammable liquid and vapor.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H412: Harmful to aquatic life with long lasting results.

Flam. Liq. 2: Flammable liquid; Hazard Category 2

Acute Tox.(oral) 4: Acute oral toxicity; Hazard Category 4

Acute Tox.(dermal) 4: Acute dermal toxicity; Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation; Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation; Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation; Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation; Hazard Category 2

STOT SE 3: Specific target organ toxicity – single exposure; Hazard Category 3

Aquatic Acute 1: Acute aquatic hazard; Hazard Category 1

Aquatic Chronic 3: Long-term aquatic hazard; Hazard Category 3