

SAFETY DATA SHEET

Carpet Spray

UNICARE (CHEMICALS) LTD

1 Identification

Product Identifier:

Carpet Spray

Other means of identification:

Not applicable.

Recommended use of the chemical and restriction on use:

For carpet cleaning

Supplier's details:

Unicare (Chemicals) Ltd,
Aradhippou Industrial Area 7101, Larnaca, Cyprus,
P.O Box 54088

Tel.: +357 24531766, +357 24533765

Fax: +357 24532111

Email: team@unicaregroup.com

Emergency phone number

1401

2 Hazard(s) identification

Classification of the substance or mixture

According to regulation (EC) No 1272/2008 [CLP]

Skin corrosion / Irritation: Hazard Category 2

Serious Eye Damage / Irritation: Hazard Category 2

GHS Label Element



Signal Word:

Warning

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

Precautionary Statement

Wash your hands thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF eye irritation persists: Get medical advice/attention.
 If skin irritation occurs: Get medical advice/attention.
 Take off contaminated clothing and wash before reuse.

Other hazards which do not result in classification

Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

Mixture

Description	- CAS Number - EINECS Number - Reach registration number	Concentration (% w/w)	Note / Classification
Alcohols, C12-14, ethoxylated, sulfates, sodium salts	- 68891-38-3 - 500-234-8 - N/A	3.8 - 5.0	Eye Dam. 1. H318; Skin Irrit. 2, H315; Aquatic Chronic 3, H412 <u>Specific Concentrations</u> ≥ 10% Eye Dam. 1 (H318) 5-10 % Eye Irrit. 2 (H319)
2-Butoxyethanol	- 111-76-2 - 203-905-0 - N/A	8.5 – 10	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4 H332; Skin Irrit. 2, H319
Isopropyl alcohol	- 67-63-0 - 200-661-7 - N/A	4 – 5	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

4 First-aid measures

Description of first aid measures

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention (if necessary).

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, and consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms/effects, acute and delayed

No known symptoms.

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5 Fire-fighting measures

Extinguishing media

Flash Point & Method

None

Suitable Extinguishing Media

Pulverized water, foam, dry chemical & carbon dioxide

Specific hazards arising from the chemical

Carbon monoxide, carbon dioxide, formaldehyde as well as other toxic vapours and gases which are common to thermal degradation (in case of fire) of organic compounds.

Special protective actions for fire-fighters

Wear self-contained breathing apparatus and full protective gear.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures see, Section 8.

Environmental precautions

No special precautions required.

Methods and materials for containment and cleaning up

For residues: Pick up with suitable absorbent material.

Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Avoid the spillage or runoff entering drains, sewers or watercourses. Flush away spillage with plenty of water.

Dispose of absorbed material in accordance with regulations.

For large amounts: Dike spillage. Pump off product.

7 Handling and storage

Precautions for safe handling

Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing.

Handle uncleaned empty containers as full ones.

Thoroughly clean/dry the installation before use.

Do not discharge the waste into the drain. Do not use compressed air for pumping over.

Use spark-/explosion proof appliances and lighting system.

Take precautions against electrostatic charges. Keep away from naked flames/heat.

Keep away from ignition sources/sparks.

Observe normal hygiene standards. Keep container tightly closed.

Protection against fire and explosion

Mark the danger area. Consider evacuation. Seal off low-lying areas. Stop engines and no smoking. No naked flames or sparks. Spark- and explosion-proof appliances and lighting equipment. Keep containers closed.

Conditions for safe storage, including any incompatibilities

Incompatible products: strong acids, strong oxidizers

Incompatible materials: direct sunlight, heat sources, sources of ignition

Heat-ignition: KEEP SUBSTANCE AWAY FROM: heat sources, ignition sources

Storage stability:

Store in a cool area. Store in a dry area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Meet the legal requirements.

Packing material:

SUITABLE MATERIAL: Teflon, polyethylene, polypropylene
 MATERIAL TO AVOID: steel with rubber inner lining, aluminium

Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

8 Exposure controls/personal protection**Control parameters****Ingredients with limit values that require monitoring at the workplace:**

Isopropanol (CAS: 67-63-0)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	200 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TWA: Time-Weighted Average concentration

STEL: Short Term Exposure Limit

PEL: Permissible Exposure Limit

2-Butoxyethanol (CAS:111-76-2)		
ACGIH	ACGIH TWA (ppm)	8-hour TWA: 25 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	8-hour TWA: 123 mg/m ³

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TWA: Time-Weighted Average concentration

STEL: Short Term Exposure Limit

PEL: Permissible Exposure Limit

Components with PNEC**CAS: 68891-38-3: Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)**

- freshwater: 0.24 mg/l
- marine water: 0.024 mg/l
- intermittent release: 0.071 mg/l
- sewage treatment plant: 10000 mg/l
- sediment (freshwater): 0.9168 mg/kg
- sediment (marine water): 0.09168 mg/kg
- soil: 7.5 mg/kg
- oral (secondary poisoning): No PNEC value available.

Components with DNEL

CAS: 68891-38-3: Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

worker: Long-term exposure-systemic effects, Inhalation: 175 mg/m³
worker: Long-term exposure-systemic effects, dermal: 2750 mg/kg
consumer: Long-term exposure-systemic effects, Inhalation: 52 mg/m³
consumer: Long-term exposure-systemic effects, dermal: 1650 mg/kg
consumer: Long-term exposure-systemic effects, oral: 15 mg/kg

CAS:111-76-2: 2-Butoxyethanol

worker: Long-term exposure-systemic effects, inhalation: 20 mg/m³
worker: Long-term exposure-non-systemic effects, dermal: 75 mg/m²
consumer: Long-term exposure-systemic effects, Inhalation: 49 mg/m³
consumer: Short-term exposure-local effects, Inhalation: 123 mg/m³
consumer: Long-term exposure-systemic effects, dermal: 38 mg/kg
consumer: Long-term exposure-systemic effects, oral: 3.2 mg/kg

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protective equipment

Respiratory protection:

Respiratory protection in case of vapour/aerosol release. (Particle filter EN 143 P2 or FFP2)

Hand protection:

Chemical resistant protective gloves. (EN 374)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374):

e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (cage goggles) (e.g. EN 166) and face shield.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work.

Handle in accordance with good industrial hygiene and safety practice.

9 Physical and chemical properties

Physical and chemical properties

General Information

- **Appearance:**
Form: Liquid

Colour: Clear

- **Odour:** Not determined
- **Odour threshold:** Not determined
- **pH-value:** 9.0 - 9.5
- **Specific gravity:** 1.00 – 1.01
- **Change in condition**
 - Melting point/Melting range:** Not determined
 - Boiling point/Boiling range:** Not determined
- **Flash point:** Not determined
- **Flammability (solid, gaseous):** Not applicable
- **Ignition temperature:** Not applicable
- **Decomposition temperature:** Not determined
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapour pressure at 20 °C:** Not determined
- **Density at 20 °C:** Not determined
- **Relative density:** Not determined
- **Relative density:** Not determined
- **Vapour density:** Not determined
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined
- **Viscosity:**
 - Dynamic:** Not determined
 - Kinematic:** Not determined

10 Stability and reactivity

Reactivity

May react violently with oxidants.

Prolonged storage/in large quantities: may form peroxides.

Chemical stability

No specific test data related to reactivity available for this product or its ingredients.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

Conditions to avoid

See SDS Section 7 - Handling and storage.

Incompatible materials

Substances to avoid:

Avoid contact with oxidising agents (e.g. nitric acid, peroxides, chromates, etc).

Strong acids

Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

In case of fire: carbon dioxide, carbon monoxide

11 Toxicological information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Toxicological (health) effects

Acute toxicity: Assessment: Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Assessment: Irritant to skin.

Serious eye damage/irritation: Assessment: Cause serious eye irritation.

Respiratory or skin sensitisation: Assessment: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Assessment: Based on available data, the classification criteria are not met.

Carcinogenicity: Assessment: Based on available data, the classification criteria are not met.

Reproductive toxicity: Assessment: Based on available data, the classification criteria are not met.

STOT-single exposure: Assessment: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Assessment: Based on available data, the classification criteria are not met.

Aspiration hazard: Assessment: No aspiration hazard expected.

Symptoms related to the physical, chemical and toxicological characteristics: Not available data.

Numerical measures of toxicity (such as acute toxicity estimates): Not available data.

Toxicological Data on: Alcohols, C12-14, ethoxylated, sulfates, sodium salts (CAS: 68891-38-3)

Acute oral toxicity:	LD50 Rat: > 2.000 - 5.000 mg/kg; OECD Test Guideline 401 (literature value) Not classified.
Acute inhalation toxicity:	The study is not necessary. Sufficient data are available from alternative routes of exposure.
Acute dermal toxicity:	LD50 Rat: > 2.000 mg/kg; OECD Test Guideline 402 (literature value). Not classified.
Skin corrosion / irritation:	Rabbit: irritating; OECD Test Guideline 404 Causes skin irritation.
Serious eye damage/eye irritation:	Rabbit: highly irritating; OECD Test Guideline 405 (literature value) Test substance: Alcohols, C12-14 , ethoxylated, sulfated, sodium salts, ≥ 10% Causes serious eye damage. Alcohols, C12-14 , ethoxylated, sulfated, sodium salts, ≥ 5% - < 10% Causes serious eye irritation Test substance: Alcohols, C12-14 , ethoxylated, sulfated, sodium salts, < 5% Not classified.
Respiratory or skin Sensitisation:	Maximisation Test (GPMT) Guinea pig: not sensitizing; OECD Test Guideline 406. Not classified.
Germ cell mutagenicity: Genotoxicity <i>in vitro</i> :	<i>In vitro</i> tests did not show mutagenic effects own test results/literature values

Genotoxicity in vivo:	In vivo tests did not show mutagenic effects (literature value). Not classified.
Carcinogenicity:	The substance has been shown to be not genotoxic, therefore it is not expected to have a carcinogenic potential. Not classified.
Reproductive toxicity:	Two-generation reproductive toxicity: Rat; drinking water NOAEL ((parents)): > 300 mg/kg (based on body weight and day) NOAEL (F1): > 300 mg/kg (based on body weight and day); OECD Test Guideline 416 (literature value)
Teratogenicity:	Not classified. Rat; Oral NOAEL: > 1.000 mg/kg (based on body weight and day) NOAEL (pregnant female): > 1.000 mg/kg (based on body weight and day); OECD Test Guideline 414 (literature value). Not classified.
STOT - single exposure:	The substance or mixture is not classified as specific target organ toxicant, single exposure.
STOT - repeated exposure:	The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Repeated dose toxicity	Rat; Oral; 90-day NOAEL: > 225 mg/kg (based on body weight and day); OECD Test Guideline 408 Target Organs: Liver Symptoms: Gastrointestinal disturbance, Liver disorders (literature value)
Aspiration hazard:	Not applicable.
Toxicological information:	The substance is metabolised and excreted.

Toxicological Data on: Isopropyl Alcohol (2-Propanol) (CAS: 67-63-0)

LD50 oral rat:

5045 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 5840 mg/kg body weight; Rat)

LD50 dermal rabbit:

12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)

LC50 inhalation rat (mg/l):

73 mg/l/4h (Rat)

ATE US (oral):

5045.000 mg/kg body weight

ATE US (dermal):

12870.000 mg/kg body weight

ATE US (vapors):

73.000 mg/l/4h

ATE US (dust, mist):

73.000 mg/l/4h

Toxicological Data on: 2-Butoxyethanol (CAS: 111-76-2)

Acute toxicity: Other toxicological data Acute Toxicity (Oral LD50): mg/kg (oral rat) 1,746
Acute Toxicity (Inhalation LC50): mg/l (vapours) (4h) 2 - 20
Acute Toxicity (Dermal LD50): mg/kg Guinea Pig > 2000.

Potential acute effects:

Inhalation: In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Ikke klassificerad som aspirationstoxisk (Not classified as asp. tox.)

Skin contact: Irritating to skin. Prolonged or frequent contact may cause redness, itching, eczema and skin cracking. Defats the skin.

Eye contact: May irritate and cause redness and pain. Causes serious eye irritation.

Ingestion: Ingestion of large amounts may cause unconsciousness. However, ingestion may cause nausea, headache, dizziness and intoxication. Ingestion may cause irritation of the gastrointestinal tract, vomiting and diarrhoea. May cause irritation to the mouth and throat.

13 Ecological information

Toxicity:

Eco toxicity

No relevant information available.

Persistence and Degradability

No relevant information available.

Bioaccumulation

No relevant information available.

Mobility in soil

No relevant information available.

Other Adverse Effects

No relevant information available.

Ecological Data on: Alcohols, C12-14, ethoxylated, sulfates, sodium salts (CAS: 68891-38-3)

Toxicity to fish:

LC50: 1 - 10 mg/l, Brachydanio rerio (zebrafish)

Aquatic invertebrates:

EC50 > 1 - 10 mg/l, Daphnia magna (OECD Guideline 202, part 1)

Aquatic plants:

EC50 > 10 - 100 mg/l, Scenedesmus subspicatus (OECD Guideline 201)

Microorganisms / Effect on activated sludge:

EC0 > 10.000 mg/l, Pseudomonas putida (DIN 38412 Part 27 (draft))

Chronic toxicity to fish:

NOEC (28 d) Oncorhynchus mykiss (rainbow trout): 0,14 mg/l; mortality; (flow-through test; OECD Test Guideline 204)

Chronic toxicity to aquatic invertebrates:

0,27 mg/l; Daphnia magna reproduction rate; flow-through test; (OECD Test Guideline 211, literature value)

Ecological Data on: Isopropyl Alcohol (2-Propanol) (CAS: 67-63-0)

LC50 fish 1:

4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)

EC50 Daphnia 1:

> 10000 mg/l (48 h; Daphnia magna)

LC50 fish 2:

9640 mg/l (96 h; Pimephales promelas; Lethal)

EC50 Daphnia 2:

13299 mg/l (48 h; Daphnia magna)

Threshold limit algae1:

> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)

Threshold limit algae 2:

1800 mg/l (72 h; Algae; Cell numbers)

Ecological Data on: 2-Butoxyethanol (CAS:111-76-2)

Acute aquatic, fish Value:

1,474 mg/l

[Method of testing: LC50 (OECD 203) Fish, species: Oncorhynchus mykiss. Duration: 96h]

Acute aquatic, algae Value:

1,840 mg/l

[Method of testing: EC50 (OECD 201), Algae, species: Pseudokirchneriella subcapitata. Duration: 72h]

Acute aquatic, Daphnia Value:

1,550 mg/l

[Method of testing: EC50 (OECD 202) Daphnia, species: Daphnia magna. Duration: 48h]

Other ecotoxicological information, Fish:

Chronic toxicity: NOEC (21 d) > 100 mg/l, Brachydanio rerio

Other ecotoxicological information, Crustaceans:

Chronic toxicity: NOEC (21 d) 100 mg/l, Daphnia magna (OECD Guideline 211)

13 Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

14 Transport information

UN Number: ADR/RID, IMDG, IATA: Not applicable.
UN Proper Shipping Name: ADR/RID, IMDG, IATA: Not applicable.
Transport hazard class(es): Not applicable
Packing group, if applicable: Not applicable
Environmental hazards: Not applicable.
Special precaution for user: Not applicable.
Transport in bulk according to Annex II of Marpol 73/78 and the IBCcode: Not applicable.

15 Regulatory information

Safety, health and environmental regulations specific for the product in question

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I:** None of the ingredients is listed.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

PBT: Persistent, Bioaccumulative and Toxic

PNEC: Predicted No-Effect Concentration

VOC: Volatile Organic Compounds (USA, EU)

vPvB: very Persistent and very Bioaccumulative

H225: Highly flammable liquid and vapor.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Fam. Liq. 2: Flammable liquid; Hazard Category 2

Acute Tox. (oral) 4: Acute oral toxicity; Hazard Category 4

Acute Tox. (dermal) 4: Acute dermal toxicity; Hazard Category 4

Acute Tox. (inhalation) 4: Acute inhalation toxicity; Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 3: Long-term aquatic hazard; Hazard Category 3